Dino-Lite Europe - Phone: - Email:

AM4113ZTL

Brand: Dino-Lite

Product Code: AM4113ZTL

Short Description

1.3 Megapixel resolution


With magnification lock

10-90x Magnification and Long working distance

Polarizer (anti-reflection)

Description

By using a special polarization filter, the AM4113ZTL is the right choice when working with high glare materials such as plastics and metals. This model also has a long working distance.



Working distance/field of view/depth of field

MAGNIFICATI WORKING		FIELD OF	FIELD OF	DEPTH OF	
ON RATE	DISTANCE	VIEW(X)	VIEW(Y)	FIELD	
20	151.0	19.6	15.6		6
30	101.0	13.0	10.4	3.4	
40	77.2	9.8	7.8	2.2	
50	64.1	7.8	6.3	1.65	
60	56.2	6.5	5.2	•	
70	51.3	5.6	4.5	•	
80	48.3	4.9	3.9	•	
90	46.6	4.3	3.5	0.8	
Listed values				Unit = mm	

may differ slightly

Specification

Specification				
Lighting				
Light/ LED type	White			
Number of LEDs	8			
LED on/off switchable:	Yes			
Infrared filter	IR cut-filter >650 nm			
Diffuser available	No			
Emission filter	No			
Polarizer	Yes, linear			
Optics				
Magnification	10-90x			
Macro zoom	No			
Working distance	Long			
Lens type	Glass with anti-reflection coating			
Sensor				
Sensor type	CMOS			
Resolution	1.3 Megapixel (1280x1024)			
Maximum frame rate	30 fps			
Compatibility				
Interface	USB 2.0			
Operating system	Windows 7, 8, 10 & 11, MacOS 10.9 and up			
Included software	DinoCapture 2.0 (Windows), DinoXcope (Mac			
	OS)			
Supported image formats (Windows)	BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX			
Supported video formats	WMV, FLV, SWF			
(Windows)	IDEC DVC			
Supported image formats (MacOS)	JPEG, PNG			
Supported video formats (MacOS)	MOV			
Imaging standards	DirectShow, UVC			
Wifi	Wireless-ready, requires the WF-10 WiFi streamer			
	(optional)			
Housing				
Housing material	Composite/ plastic housing			
Magnification lock	Yes			
Dimensions	10.5cm (L) x 3.2cm (D)			
Weight	105g			

Cable length	1.8m	
Features		
Special feature	No	
Measurement	Yes	
Calibration	Yes	
Microtouch sensor	Yes	
ESD safe	No	
Information		
Package contents	Microscope, carry pouch, software CD, calibration	
	target, ZT-Z-CC1 cap closure, user manual	
Warranty information	2 years European warranty	
Regulatory approval	CE, FCC, ROHS	
Price range	€400,00 - €600,00	