Dino-Lite Europe - Phone: - Email:

## **AM4013MZT4**

**Brand:** Dino-Lite

**Product Code:** AM4013MZT4



#### **Short Description**

1.3 Megapixel resolution Robust metal housing 400-470x magnification Polarizer (anti-reflection)

#### **Description**

The AM4013MZT4 with a high magnification of 400~470x reveals even the smallest details on all kinds of objects. The built-in, switchable polarizer makes the AM4013MZT4 the right choice for working with high glare materials such as jewelry, plastics and metals. The aluminum housing offers enhanced protection and durability and has the best look and feel.







# Working distance/field of view/depth of field

| MAGNIFICATI          | WORKING  | FIELD OF | FIELD OF | DEPTH OF  |
|----------------------|----------|----------|----------|-----------|
| ON RATE              | DISTANCE | VIEW(X)  | VIEW(Y)  | FIELD     |
| <b>Listed values</b> |          |          |          | Unit = mm |
| may differ           |          |          |          |           |
| slightly             |          |          |          |           |
| 430                  | -0.45    | 0.91     | 0.73     | 0.1       |
| 440                  | 0.4      | 0.89     | 0.71     | 0.1       |
| 450                  | 1.35     | 0.87     | 0.7      | 0.1       |
| 460                  | 2.3      | 0.85     | 0.68     | 0.1       |
| 470                  | 3.15     | 0.83     | 0.67     | 0.1       |
|                      |          |          |          |           |

## **Specification**

| Specification          |   |  |  |  |
|------------------------|---|--|--|--|
| Lighting               |   |  |  |  |
| Light/ LED type        | White                                     |  |  |  |
| Number of LEDs         | 8   |  |  |  |
| LED on/off switchable: | Yes                                       |  |  |  |
| Infrared filter        | IR cut-filter >650 nm                     |  |  |  |
| Diffuser available     | No  |  |  |  |
| Emission filter        | No  |  |  |  |
| Polarizer              | Yes, linear                               |  |  |  |
| Optics                 |   |  |  |  |
| Magnification          | 400-470x                                  |  |  |  |
| Macro zoom             | No  |  |  |  |
| Working distance       | Standard                                  |  |  |  |
| Lens type              | Glass with anti-reflection coating        |  |  |  |
| Sensor                 |   |  |  |  |
| Sensor type            | CMOS                                      |  |  |  |
| Resolution             | 1.3 Megapixel (1280x1024)                 |  |  |  |
| Maximum frame rate     | 30 fps                                    |  |  |  |
| Compatibility          |   |  |  |  |
| Interface              | USB 2.0                                   |  |  |  |
| Operating system       | Windows 7,8,10 & 11, MacOS 10.9 and up    |  |  |  |
| Included software      | DinoCapture 2.0 (Windows), DinoXcope (Mac |  |  |  |

|                         | OS)   |  |
|-------------------------|---|--|
| Supported image formats | BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA,           |  |
| (Windows)               | PCX, MNG, WBMP, JP2, JPC, PGX                     |  |
| Supported video formats | WMV, FLV, SWF                                     |  |
| (Windows)               |   |  |
| Supported image formats | JPEG, PNG   |  |
| (MacOS)                 |   |  |
| Supported video formats | MOV   |  |
| (MacOS)                 |   |  |
| Imaging standards       | DirectShow, UVC                                   |  |
| Wifi                    | Wireless-ready, requires the WF-10 WiFi streamer  |  |
|                         | (optional)  |  |
| Housing                 |   |  |
| Housing material        | Metal housing                                     |  |
| Magnification lock      | No  |  |
| Dimensions              | 10.5cm (L) x 3.2cm (D)                            |  |
| Weight                  | 140g  |  |
| Cable length            | 1.8m  |  |
| Features                |   |  |
| Special feature         | No  |  |
| Measurement             | Yes   |  |
| Calibration             | Yes   |  |
| Microtouch sensor       | Yes   |  |
| ESD safe                | Yes   |  |
| Information             |   |  |
| Package contents        | Microscope, carry pouch, software CD, calibration |  |
|                         | target, ZT-Z-CC1 cap closure, user manual         |  |
| Warranty information    | 2 years European warranty                         |  |
| Regulatory approval     | CE, FCC, ROHS, UKCA – available upon request      |  |
|                         | <ul><li>marketing@dino-lite.eu</li></ul>          |  |
| Price range             | €600,00 - €800,00                                 |  |
|                         |   |  |

# **Product Gallery**